



BURLINGTON COLLECTION

The new Burlington Burr will not just bring the orchestra to your home but make the walls disappear and take you directly to the concert hall.

Based on the concept of benchmark precision this new floor-stander will deliver audio information well beyond 20Khz with-out the need for a super tweeter paving the way for SACD and DVD formats with extended bandwidths.

Bass extension is equally stunning with Magnesium alloy diaphragms and shielded ultra low distortion motors allowing perfect integration into any 2-channel or home cinema environment.

A substantially braced cabinet houses two sophisticated doped magnesium coned drivers in a D'Appolito design and a true reference quality ribbon tweeter complimented with silver plated internal cable and hard wired to a unique cross-over employing the best capacitors and inductors finally being connected using gold plated connector posts from WBT or Eichman.

Fully customisable and gradeable, this beautiful loudspeaker will grace any living space and provide musical harmony for many years.

TECHNICAL SPECIFICATIONS

| | |
|--------------------|---|
| Technology | MDF matrix construction |
| Description | 2 way, linear phase, free ported enclosure |
| Drive Units | 2 x 174 mm Magnesium alloy cone bass/mid range uit 1 x Low mass Ribbon high precision tweeter |
| Frequency Response | 35Hz to 45KHz +/- 2dB on axis |
| Impedance | 4 Ohms nominal, 3 Ohms minimum |
| Sensitivity | 89dB spl at 1 metre on axis. 2.83V input |
| Crossover | 2nd order bass roll-off 2nd order midrange and tweeter |
| Power Handling | 150W peak un-clipped programme |
| Dimensions | Height - 106cm Width - 22cm Depth - 28cm |
| Net Weight | 32 Kg |
| Finishes | Standard finish available in black hide and oak. Bespoke options available in various hides and hardwood. Mundorf capacitor and Cryo treated internal wiring upgrades available upon request. |